

FOUNDATION LAYOUT FOR CHARTWELL

PLOT 62 ONLY

NOTE:-FFL OF GARAGE SHOWN ON GA PLAN IS LEVEL AT ENTRANCE (SUPPLIED BY CAMPBELL REITH) REFER TO CAMPBELL REITH DRAWINGS FOR FALLS IN FINISHES AND FFL AT REAR OF GARAGE

PLOT NOS.	HOUSE FFL	GARAGE FFL	SSL	TOP OF FOUNDATION LEVEL	BTM. OF FOUNDATION LEVEL
62	166.380	166.230	166.155	165.555	AS SHOWN ON PLAN

LEGEND

▶ B&B

GENERAL INTERNAL GROUND FLOOR:-DENOTES SPAN OF SUSPENDED 150 DEEP PRESTRESSED CONCRETE BEAM AND STRUCTURAL EPS FLOOR OVER USING STRUCTURAL GRADE EPS AND 75 THICK STRUCTURAL CONCRETE GRADE RC32/40 TOPPING REINFORCED WITH A142 MESH WITH 40 COVER IN

NOTE:-

ALL FOUNDATIONS TO BE 500mm

BE CHECKED BY QUALIFIED

GEOTECHNICAL ENGINEER ON

BELOW DESSICATED SOIL. THIS TO

B & B

HEAVY

GARAGES AND BIN/CYCLE STORE FLOOR:DENOTES SPAN OF SUBSTITE

DENOTES SPAN OF SPAN OF SUBSTITE

DENOTES SPAN OF SPAN DEEP PRESTRESSED CONCRETE BEAM AND BLOCK FLOOR OVER USING STRUCTURAL GRADE TOP EPS INSULATION SHEET & 75 MIN. THICK STRUCTURAL CONCRETE GRADE RC32/40 TOPPING LAID TO FALLS REINFORCED WITH A142 MESH WITH 40 COVER IN TOP. MASONRY INFILL BLOCKS BETWEEN PC SLEEPER BEAMS TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 7N/mm².

Do not scale from this drawing. SAFETY HEALTH AND ENVIRONMENTAL INFORMATION

WITH THE TYPES OF WORK DETAILED ON THIS DRAWING, NOTE THE FOLLOWING RISKS AND INFORMATION.

RISKS LISTED HERE ARE NOT EXHAUSTIVE. REFER TO DESIGN

IN ADDITION TO THE HAZARD/RISKS NORMALLY ASSOCIATED

CONSTRUCTION

ASSESSMENT FORM NO.

DEMOLITION

FOR INFORMATION RELATING TO USE, CLEANING AND MAINTENANCE SEE THE HEALTH AND SAFETY FILE

IT IS ASSUMED THAT ALL WORKS WILL BE CARRIED OUT BY A COMPETENT CONTRACTOR WORKING, WHERE APPROPRIATE, TO AN APPROVED METHOD STATEMENT.

- DO NOT SCALE THIS DRAWING. WORK TO FIGURED DIMENSIONS ONLY. ALL
- DIMENSIONS ARE IN MILLIMETRES (mm). ALL LEVELS IN METRES (m). THIS DRAWING TO BE READ IN CONJUNCTION WITH AND CHECKED AGAINST ALL OTHER RELEVANT ARCHITECTS, ENGINEERS AND SPECIALISTS DRAWINGS,

SPECIFICATIONS & CONTRACT DOCUMENTS.

- CONFIRM ALL LEVELS, DIMENSIONS, DETAILS ETC, BEFORE WORK COMMENCES AND REPORT ANY DISCREPANCIES OR OMISSIONS IMMEDIATELY.
- ALL WORK & MATERIALS TO COMPLY WITH THE RELEVANT BRITISH STANDARDS, CODES OF PRACTICE AND THE BUILDING REGULATIONS.
- THE ENGINEER IS TO BE INFORMED IF ANY DETAIL INDICATED OR IMPLIED ON THIS DRAWING CAN NOT BE MAINTAINED.
- FOR SETTING OUT OF WALLS, STRUCTURAL OPENINGS AND SERVICE HOLES REFER TO ARCHITECT'S DRAWINGS.
- ALL DPC's, DPM's, INSULATION, CAVITY BARRIERS, WALL AND FLOOR FINISHES TO ARCHITECT'S DETAILS. PROVIDE AIR VENTS/BRICKS AT CENTRES TO SUIT ARCHITECT'S DETAILS TO INTERNAL AND EXTERNAL WALLS TO ALLOW CROSS
- THE CONTRACTOR SHALL ENSURE THAT STABILITY OF THE BUILDING AND ADJACENT PREMISES IS MAINTAINED AT ALL STAGES OF CONSTRUCTION. COMPETENT SPECIALIST SUB-CONTRACTORS SHALL DESIGN, INSTALL AND MAINTAIN ALL NECESSARY TEMPORARY WORKS AND PROGRAMME THE JOB ACCORDINGLY IN A SAFE MANNER.
- FOR LOCATION OF SERVICES THROUGH FLOOR AND WALLS REFER TO ARCHITECTS /SERVICE ENGINEERS DETAILS.
- . ALL FOUNDATION DEPTHS ARE TO BE AS NOTED BUT ARE SUBJECT TO FINAL INSPECTION ON SITE. IF ACTIVE ROOT GROWTH IS APPARENT AT FOUNDING LEVEL THEN THE FOUNDATION MUST BE DEEPENED TO EXTEND 300mm BELOW ANY ACTIVE ROOTS.
- WHERE A FOUNDATION PASSES CLOSE TO A SEWER, DRAIN TRENCH OR TRIAL PIT THE FOUNDATION IS TO BE SUCH THAT IT'S UNDERSIDE IS BELOW A LINE PROJECTED UP AT 45° FROM THE NEAREST BOTTOM CORNER OF THE DRAIN TRENCH, SEWER OR TRIAL PIT.

REFER TO ARCHITECTS DRAWINGS FOR SETTING OUT AND GLOBAL POSITIONING OF ALL MASONRY WALLS SHOWN ON THIS DRAWING

REFER TO ARCHITECTS DRAWINGS FOR SIZE & POSITION OF ALL SERVICE HOLES AND SERVICES.

TENDER ISSUE

12.09.23 ISSUED FOR TENDER SUITE A, OAK HOUSE LONDON ROAD SEVENOAKS DANDARA LTD. TN13 1AF

Tel: 01732 460 142 sevenoaks@fairhurst.co.uk

STEEL CROSS, CROWBOROUGH,

EAST SUSSEX

16.08.24 LEVELS UPDATED

CHÄRTWELL SUBSTRUCTURE G.A. PLAN PLOT 62 (OPTION 2)

TENDER AUGUST 2023 SEPTEMBER 2023 SEPTEMBER 2023

P02

152987-SCC-FRH-XX-FN-DR-S-4116