

FOUNDATION LAYOUT FOR GOODWOOD

PLOT 77 ONLY

NOTE:-FFL OF GARAGE SHOWN ON GA PLAN IS LEVEL AT ENTRANCE (SUPPLIED BY CAMPBELL REITH) REFER

PLOT NOS.	HOUSE FFL	GARAGE FFL	SSL	TOP OF FOUNDATION LEVEL	BTM. OF FOUNDATION LEVEL
77	167.170	167.020	166.945	166.345	AS SHOWN ON PLAN

TO CAMPBELL REITH DRAWINGS FOR FALLS IN FINISHES AND FFL AT REAR OF GARAGE

LEGEND

B&B **GENERAL INTERNAL GROUND FLOOR:-**

DENOTES SPAN OF SUSPENDED 150 DEEP PRESTRESSED CONCRETE BEAM AND STRUCTURAL EPS FLOOR OVER USING STRUCTURAL GRADE EPS AND 75 THICK STRUCTURAL CONCRETE GRADE RC32/40 TOPPING REINFORCED WITH A142 MESH WITH 40 COVER IN

B & B
HEAVY

GARAGES AND BIN/CYCLE STORE FLOOR:DENOTES SPAN OF CLOSE. DEEP PRESTRESSED CONCRETE BEAM AND BLOCK FLOOR OVER USING STRUCTURAL GRADE TOP EPS INSULATION SHEET & 75 MIN. THICK STRUCTURAL CONCRETE GRADE RC32/40 TOPPING LAID TO FALLS REINFORCED WITH A142 MESH WITH 40 COVER IN TOP. MASONRY INFILL BLOCKS BETWEEN PC SLEEPER BEAMS TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 7N/mm².

Do not scale from this drawing.

SAFETY HEALTH AND ENVIRONMENTAL INFORMATION

IN ADDITION TO THE HAZARD/RISKS NORMALLY ASSOCIATED

NOTE THE FOLLOWING RISKS AND INFORMATION.

WITH THE TYPES OF WORK DETAILED ON THIS DRAWING,

RISKS LISTED HERE ARE NOT EXHAUSTIVE. REFER TO DESIGN ASSESSMENT FORM NO.

CONSTRUCTION

DEMOLITION

FOR INFORMATION RELATING TO USE, CLEANING AND MAINTENANCE SEE THE HEALTH AND SAFETY FILE

IT IS ASSUMED THAT ALL WORKS WILL BE CARRIED OUT BY A COMPETENT CONTRACTOR WORKING, WHERE APPROPRIATE, TO AN APPROVED METHOD STATEMENT.

- DO NOT SCALE THIS DRAWING. WORK TO FIGURED DIMENSIONS ONLY. ALL
- THIS DRAWING TO BE READ IN CONJUNCTION WITH AND CHECKED AGAINST ALL OTHER RELEVANT ARCHITECTS, ENGINEERS AND SPECIALISTS DRAWINGS, SPECIFICATIONS & CONTRACT DOCUMENTS.

DIMENSIONS ARE IN MILLIMETRES (mm). ALL LEVELS IN METRES (m).

- CONFIRM ALL LEVELS, DIMENSIONS, DETAILS ETC, BEFORE WORK COMMENCES AND REPORT ANY DISCREPANCIES OR OMISSIONS IMMEDIATELY.
- ALL WORK & MATERIALS TO COMPLY WITH THE RELEVANT BRITISH STANDARDS, CODES OF PRACTICE AND THE BUILDING REGULATIONS.
- THE ENGINEER IS TO BE INFORMED IF ANY DETAIL INDICATED OR IMPLIED ON THIS DRAWING CAN NOT BE MAINTAINED.
- FOR SETTING OUT OF WALLS, STRUCTURAL OPENINGS AND SERVICE HOLES REFER TO ARCHITECT'S DRAWINGS.
- ALL DPC's, DPM's, INSULATION, CAVITY BARRIERS, WALL AND FLOOR FINISHES TO ARCHITECT'S DETAILS. PROVIDE AIR VENTS/BRICKS AT CENTRES TO SUIT ARCHITECT'S DETAILS TO INTERNAL AND EXTERNAL WALLS TO ALLOW CROSS
- THE CONTRACTOR SHALL ENSURE THAT STABILITY OF THE BUILDING AND ADJACENT PREMISES IS MAINTAINED AT ALL STAGES OF CONSTRUCTION. COMPETENT SPECIALIST SUB-CONTRACTORS SHALL DESIGN, INSTALL AND MAINTAIN ALL NECESSARY TEMPORARY WORKS AND PROGRAMME THE JOB ACCORDINGLY IN A SAFE MANNER.
- FOR LOCATION OF SERVICES THROUGH FLOOR AND WALLS REFER TO ARCHITECTS /SERVICE ENGINEERS DETAILS.
- . ALL FOUNDATION DEPTHS ARE TO BE AS NOTED BUT ARE SUBJECT TO FINAL INSPECTION ON SITE. IF ACTIVE ROOT GROWTH IS APPARENT AT FOUNDING LEVEL THEN THE FOUNDATION MUST BE DEEPENED TO EXTEND 300mm BELOW ANY ACTIVE ROOTS.
- WHERE A FOUNDATION PASSES CLOSE TO A SEWER, DRAIN TRENCH OR TRIAL PIT THE FOUNDATION IS TO BE SUCH THAT IT'S UNDERSIDE IS BELOW A LINE PROJECTED UP AT 45° FROM THE NEAREST BOTTOM CORNER OF THE DRAIN TRENCH, SEWER OR TRIAL PIT.

REFER TO ARCHITECTS DRAWINGS FOR SETTING OUT AND GLOBAL POSITIONING OF ALL MASONRY WALLS SHOWN ON THIS DRAWING

REFER TO ARCHITECTS DRAWINGS FOR SIZE & POSITION OF ALL SERVICE HOLES AND SERVICES

CONSTRUCTION ISSUE

Е	A 1 E	Client:			
Rev.	1 12.09.23 ISSUED FOR TENDER		Drw	n. Chkd	I. Ap
P01			JM	PL	Р
P02			IS	PL	Р
C01	25.04.25	25.04.25 ARCHITECTS BACKGROUND UPDATED. ISSUED FOR CONSTRUCTION.			

SUITE A OAK HOUSE LONDON ROAD SEVENOAKS TN13 1AF Tel: 01732 460 142

DANDARA LTD.

sevenoaks@fairhurst.co.uk

STEEL CROSS, CROWBOROUGH, EAST SUSSEX

GOODWOOD SUBSTRUCTURE G.A. PLAN PLOT 77 (OPTION 2)

Scale at A1: 1:50	Status: TENDER					
Drawn: JM	Checked: PL	Approved: PS				
Date: AUGUST 2023	Date: SEPTEMBER 2023	Date: SEPTEMBER 2023				
Drawing No :	=	Revision				

152987-SCC-FRH-XX-FN-DR-S-4145

C01