SUBSTRUCTURE BLOCK PLAN
PLOTS 189-191

WHEN A MASONRY PIER IS A NON BRICK DIMENSION, IF THE LENGTH CAN ACCOMMODATE +/- 1.5mm THEN ADJUST A STANDARD 10mm MORTAR JOINT TO SUIT. IF OUTSIDE OF THESE PARAMETERS, THEN A CUT BRICK IS TO BE USED.



Key:

- SW Direct drainage connection for Kitchen Sink
- BW Direct drainage connection for Wash Hand Basin
- WC Direct drainage connection for WC
- FS Direct drainage connection for Future Shower
- BC Direct drainage connection for boiler condensate
- SVP Soil and Vent Pipe
- SS Stub stack
- AAV Air admittance valve
- W Water entry point
- GP Gas point
- External water tap
- Telecom entry point
- Consumer service unit.
- Network access point.
- RWP Rain water downpipe
- G Semi-recessed gas meter box
- E Semi-recessed electric meter box
- Extract vent
- Cavity Barrier to party wall / external wall junction - to extend to top of foundation level.
- AB Air brick

Wall Legend:

SUBSTRUCTRE WALLS

- 102.5mm facing brickwork.
- 140mm Aircrete blockwork 3.6N/mm2 (450-800kg/m3, 0.15W/mk).

Part M COMPLIANCE NOTE
Plots noted as M4(2) are required to have a front and rear level threshold and compliant rear door.
For all M4(1) plots level thresholds required to front doors only with the exception of where stepped access is provided to the front door therefore level access is required at the rear door. Refer to Civil Engineers levels drawing for M4(1) plots requiring the above.

SUB STRUCTURE NOTES :

1. THIS DRAWING MUST NOT BE SCALED.
2. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER PROJECT DRAWINGS
3. ALL DETAILS AND DRAWINGS MUST BE READ IN CONJUNCTION WITH THE *PROJECT SPECIFIC CONSTRUCTION SPECIFICATION.
4. BEAM AND BLOCK / RAFT FOUNDATIONS TO STRUCTURAL ENGINEER / SPECIALIST DESIGN.
5. FOR DETAILS OF CAST INSITU POWERFLOATED SUSPENDED GROUND FLOOR SLAB, SEE SPECIALIST DRAWINGS.
6. DATUM 1 (MASONRY CONSTRUCTION ONLY) = FINISHED FLOOR LEVEL. TOP OF FLOATING SLAB, SUSPENDED SLAB AND RAFT FOUNDATION TO BE LEVEL WITH DPC (INSOLATION POSITIONED UNDER SLABS).
7. FOUNDATION WIDTHS AND DEPTHS TO BE DETERMINED BY THE STRUCTURAL ENGINEER, BASED ON THE SITE INVESTIGATION REPORT / WALL FOUNDATION LOADS TO BE AGREED BY THE BUILDING CONTROL ENGINEER.
8. CHECK SOIL REPORT FOR SPECIAL REQUIREMENTS E.G. PRECAUTIONS NECESSARY FOR SULPHATES IN SOIL ETC.
9. GAS PIPES TO RUN IN GROUND FLOOR INSULATION OR, IF GROUND FLOOR IS POWER FLOATED, WITHIN FIRST FLOOR CARCASS.

Notes
- Copyright in this drawing remains the property of BM3 Architecture Limited.
- Do not scale this drawing. Work to figured dimensions only.
- Contractors and consultants are to advise BM3 Architecture Limited of any discrepancies.

IMPORTANT NOTE

Revision	Date	By Chkd
P1 Preliminary first issue.	01.07.24	DA CF
P2 Basin waste water pop-up added.	20.01.25	DA CF

PRELIMINARY

Client

Project
BURGESS HILL
FAIRBRIDGE WAY

CISfb Element

Drawing
PLOTS 189-191
SUBSTRUCTURE
BLOCK PLANS

Drawn by	Checked
DA	CF
Scale	Dated
1:50@A1	01.12.23
Job No.	Drawing No. / Revision
71978	189-191-200 P2

Birmingham Office
28 Pickford Street, Digbeth, Birmingham, B5 5QH
T. 0121 633 0000 F. 0121 633 0300 E. design@bm3.co.uk

BM3