



WHEN A MASONRY PIER IS A NON BRICK DIMENSION,
IF THE LENGTH CAN ACCOMMODATE $\pm 1.5\text{mm}$
THEN ADJUST A STANDARD 10mm MORTAR JOINT TO
SUIT. IF OUTSIDE OF THESE PARAMETERS, THEN A
CUT BRICK IS TO BE USED

ALL STRUCTURAL STEEL ELEMENTS TO BE DESIGN
AND SPECIFICATION, TO ACHIEVE MIN.1HR FIRE
RESISTANCE VIA INTUMESCENT PAINT

DOORSETS AND WINDOWS AS TO BE DESIGNED
IN ACCORDANCE WITH APPROVED DOCUMENT O
SECTIONS 3.6 to 3.11: 2021

1. LOCATION OF HOT WATER CYLINDER UNDER STAIR TBC
2. CONFIRM DOOR CLEARANCE FOR CYLINDER MAINTENANCE
3. RADIATOR SIZE IN ABEYANCE, SUBJECT TO SPECIALIST DESIGNER'S CALCULATION

Taylor Wimpey UK Ltd
Gate House, Turnpike Road,
High Wycombe, Bucks HP12 3NR
Tel 01494 558323 Fax 01494 885663
www.taylorwimpey.com